



S.K.Wiring Products Ltd  
Unit 5 Denton Business Park  
Windmill Lane  
Denton  
Manchester  
M34 3SP  
UK

[www.skwiring.co.uk](http://www.skwiring.co.uk)  
[sales@skwiring.co.uk](mailto:sales@skwiring.co.uk)  
Tel : +44 (0)161 320 9237  
Fax :+44 (0)161 230 3663

## **Data Sheet**

### **Product description.**

4 Core RTD 7/0.2mm Tinned Copper Wire High Temp PVC Insulated.

### **Applicable standards**

None.

### **Construction.**

7 strands of 0.2mm Tinned copper wire Bunched.

4 core insulated in high temp PVC compound ( 105 degreec C) 2 red 2 white

4 Core laid up in rotation 2 x red 2x white

Tinned Copper braided Screen >85% coverage

High Temp PVC insulated (105 degrees C)

### **Conductor material.**

Core 1 Red Tinned Copper 7/0.2mm ( 0.22mm<sup>2</sup> )

Core 2 Red Tinned Copper 7/0.2mm ( 0.22mm<sup>2</sup> )

Core 3 White Tinned Copper 7/0.2mm ( 0.22mm<sup>2</sup> )

Core 4 White Tinned Copper 7/0.2mm ( 0.22mm<sup>2</sup> )

### **Insulation Maximum operating Temperature.**

105 Degrees C

**Health and Safety information.**

No personal protective equipment required when used under normal operating conditions. Product represents no health risk when used under normal conditions

In case of fire use water

In case of smoke inhalation during combustion remove casualty to fresh air and seek medical attention. Fumes from fire will include HCL gas (hydrochloric acid), some HCL residue may remain after fire, care should be taken with burnt or fire exposed cables to avoid skin or eye contact. If contact is suspected flush the area with copious amounts of fresh water and seek medical attention.

In case of ingestion seek medical attention