

S.K.Wiring Products Ltd Unit 5 Denton Business Park Windmill Lane Denton Manchester M34 3SP UK

www.skwiring.co.uk sales@skwiring.co.uk Tel:+44(0)1613209237 Fax:+44(0)1612303663

# Data Sheet

## Product description.

0.5 mm Type K Glass lapped and braided pair laid flat Glass Braided Varnished, H.T Glass

# **Applicable standards**

BS 4937 BSEN 60584.2 relevant parts BSEN 60584.1 Class 1 All comparable international standards.

#### Construction.

Single strand of 0.5 mm diameter wire.

Each leg double glass lapped and varnished glass braided and varnished laid flat glass braided and varnished with Silicone Impregnating resin.

Conductor material.

Positive leg - Nickel/Chrome 
Negative leg - Nickel/Aluminium -

# **Insulation Maximum operating Temperature.**

750 degrees C

# Health and Safety information.

No personal protective equipment required when used under normal operating conditions. Product represents no health risk when used under normal conditions

In case of fire use water

In case of smoke inhalation during combustion remove casualty to fresh air and seek medical attention.

In case of ingestion seek medical attention

Good industrial hygiene practices should be followed.

If skin irritation occurs area should be flushed with cold water

If glass dust is produced due to rough handling it should be washed off immediately. In case of contact with eyes flush with copious amounts of clean water and seek medical attention.