



S.K.Wiring Products Ltd
Unit 5 Denton Business Park
Windmill Lane
Denton
Manchester
M34 3SP
UK

www.skwiring.co.uk
sales@skwiring.co.uk
Tel : +44 (0)161 320 9237
Fax :+44 (0)161 230 3663

Data Sheet

Product description.

7/0.2mm Type K PVC Alu/Myler IEC Thermocouple Cable.
Nominal OD 4.6mm

Applicable standards

BS 4937
BSEN 60584.2 relevant parts
BS 6746
All comparable international standards.

Construction.

Seven Strands of 0.2mm OD thermocouple alloys.
Each leg bunched
PVC extruded with high temp PVC (Green / White)
Pair twisted with a drain wire
Alum/polyester taped
High temp. PVC extruded overall (Green)

Conductor material.

Positive leg - Nickel/Chrome - Insulated Green
Negative leg - Nickel/Aluminium - Insulated White

Insulation Maximum operating Temperature.

105 Degrees C

Health and Safety information.

No personal protective equipment required when used under normal operating conditions. Product represents no health risk when used under normal conditions

In case of fire use water

In case of smoke inhalation during combustion remove casualty to fresh air and seek medical attention.

In case of ingestion seek medical attention

Good industrial hygiene practices should be followed.